

PnP COLORME : Fluorescence image deconvolution microscopy using a Plug and Play Denoiser

Vasiliki Stergiopoulou

(Morpheme team, I3S Laboratory, France)

In collaboration with:

Luca Calatroni & Laure Blanc-Féraud

(Morpheme team, I3S Laboratory, France)

Sébastien Schaub

(LBDV, Sorbonne Université, France)

Subhadip Mukherjee & Carola-Bibiane Schönlieb

(DAMTP, University of Cambridge, UK)

Mathematical Models for Plug-and-play Image Restoration



Table of Contents

Introduction


COLORME

PnP-COLORME


Preliminary Results

Conventional Fluorescence Microscopy Limitations

- Lateral resolution is limited by light diffraction phenomena





- Smallest resolvable distance (Rayleigh Criterion): $d = \frac{0.61\lambda}{NA}$ ($\approx 200nm$)
 λ : emission wavelength, NA : Numerical Aperture.



Fluctuation-based Super-Resolution Methods

We want:

- ▶ Use of standard equipment / conventional fluorophores
- ▶ Harmless excitation levels / no sample fixation
- ▶ Improved temporal resolution





Fluorophore states


Fluctuation-based Super-Resolution Methods

We want:

- ▶ Use of standard equipment / conventional fluorophores
- ▶ Harmless excitation levels / no sample fixation
- ▶ Improved temporal resolution



Fluorophore states




Temporal profile of a pixel


Fluctuation-based Super-Resolution Methods



SOFI (Dertinger *et al.*, '09)
Super resolution Optical Fluctuation Imaging



SRRF (Gustafsson *et al.*, '16)
Super-Resolution Radial Fluctuations




SPARCOM (Solomon *et al.*, '19)
SPARsity based super-resolution COrrelation Microscopy

LSPARCOM (Dardikman-Yoffe *et al.*, '20)
Learned SPARCOM

COLORME (Stergiopoulou *et al.*, '21, '22)


COVariance-based ℓ_0 super-Resolution Microscopy with intensity Estimation

- ▶ Exploits sparsity in the covariance domain
- ▶ Estimates real intensity values
- ▶ Does not have artifacts
- ▶ Extends to 3D (3D MA-TIRF COLORME)




Simulated Data


GT image




COL0RME-CEL0




COL0RME- ℓ_1




SRRF



SPARCOM



LSPARCOM




Real TIRF Data

\bar{y}

COL0RME-CEL0

COL0RME- ℓ_1



SRRF

SPARCOM

LSPARCOM




Table of Contents

Introduction


COLORME

PnP-COLORME

Preliminary Results

$$\mathbf{Y}_{\mathbf{t}} \in \mathbb{R}^{N \times N}$$

$$\mathbf{X}_{\mathbf{t}} \in \mathbb{R}^{L \times L}$$




$$\begin{aligned} q &= 4 \\ L &= qN \end{aligned}$$

$$= \left(\begin{array}{c} \mathbf{H} \\ \text{[Heatmap of H]} \end{array} * \right)_{\downarrow q} + \mathbf{N}_{\mathbf{t}} + \mathbf{B}$$

$$\mathbf{Y}_{\mathbf{t}} = M_q(H(\mathbf{X}_{\mathbf{t}})) + \mathbf{N}_{\mathbf{t}} + \mathbf{B} \xrightarrow{\text{vec}(\cdot)} \mathbf{y}_{\mathbf{t}} = \Psi \mathbf{x}_{\mathbf{t}} + \mathbf{n}_{\mathbf{t}} + \mathbf{b}, \quad \forall t = 1, \dots, T$$

$$\mathbf{Y}_t \in \mathbb{R}^{N \times N}$$

$$\mathbf{X}_t \in \mathbb{R}^{L \times L}$$



$$\begin{aligned} q &= 4 \\ L &= qN \end{aligned}$$

$$= \left(\begin{array}{c} \mathbf{H} \\ \text{[Heatmap of H]} \end{array} * \right)_{\downarrow q} + \mathbf{N}_t + \mathbf{B}$$

$$\mathbf{Y}_t = M_q(H(\mathbf{X}_t)) + \mathbf{N}_t + \mathbf{B} \xrightarrow{\text{vec}(\cdot)} \mathbf{y}_t = \Psi \mathbf{x}_t + \mathbf{n}_t + \mathbf{b}, \quad \forall t = 1, \dots, T$$


Reformulate the model in the **Covariance Domain**:

$$\mathbf{R}_y = \Psi \mathbf{R}_x \Psi^T + \mathbf{R}_n$$

$$\begin{aligned} \mathbf{R}_y &\approx \frac{1}{T-1} \sum_{t=1}^T (\mathbf{y}_t - \bar{\mathbf{y}})(\mathbf{y}_t - \bar{\mathbf{y}})^T \\ &\in \mathbb{R}_+^{N^2 \times N^2} \end{aligned}$$

$$\mathbf{Y}_t \in \mathbb{R}^{N \times N}$$

$$\mathbf{X}_t \in \mathbb{R}^{L \times L}$$



$$\begin{matrix} q=4 \\ L=qN \end{matrix}$$

$$= \left(\begin{matrix} \mathbf{H} \\ \text{[Heatmap of H]} \end{matrix} * \right) \downarrow_q + \mathbf{N}_t + \mathbf{B}$$

$$\mathbf{Y}_t = M_q(H(\mathbf{X}_t)) + \mathbf{N}_t + \mathbf{B} \xrightarrow{\text{vec}(\cdot)} \mathbf{y}_t = \Psi \mathbf{x}_t + \mathbf{n}_t + \mathbf{b}, \quad \forall t = 1, \dots, T$$

Reformulate the model in the **Covariance Domain**:


$$\mathbf{R}_y = \Psi \mathbf{R}_x \Psi^T + \mathbf{R}_n$$

- ▶ \mathbf{R}_x is diagonal: $\mathbf{r}_x = \text{diag}(\mathbf{R}_x) \in \mathbb{R}_+^{L^2}$
- ▶ $\mathbf{R}_n = s\mathbf{I}$, if $\mathbf{n}_t \sim \mathcal{N}(\mathbf{0}, s\mathbf{1}_{N^2})$
- ▶ $\Omega = \{i : (\mathbf{r}_x)_i \neq 0\} = \{i : \mathbf{x}_i \neq 0\}$

$$\mathbf{R}_y \approx \frac{1}{T-1} \sum_{t=1}^T (\mathbf{y}_t - \bar{\mathbf{y}})(\mathbf{y}_t - \bar{\mathbf{y}})^T \in \mathbb{R}_+^{N^2 \times N^2}$$

$$\mathbf{Y}_t \in \mathbb{R}^{N \times N}$$

$$\mathbf{X}_t \in \mathbb{R}^{L \times L}$$



$$q=4$$

$$L=qN$$

$$= \left(\begin{array}{c} \mathbf{H} \\ \text{[Heatmap of H]} \end{array} * \right) \downarrow_q + \mathbf{N}_t + \mathbf{B}$$

$$\mathbf{Y}_t = M_q(H(\mathbf{X}_t)) + \mathbf{N}_t + \mathbf{B} \xrightarrow{\text{vec}(\cdot)} \mathbf{y}_t = \Psi \mathbf{x}_t + \mathbf{n}_t + \mathbf{b}, \quad \forall t = 1, \dots, T$$

Reformulate the model in the **Covariance Domain**:

$$\mathbf{R}_y = \Psi \mathbf{R}_x \Psi^T + \mathbf{R}_n \xrightarrow{\text{vec}(\cdot)} \boxed{\mathbf{r}_y = (\Psi \odot \Psi) \mathbf{r}_x + s \mathbf{I}_v}$$

► \mathbf{R}_x is diagonal: $\mathbf{r}_x = \text{diag}(\mathbf{R}_x) \in \mathbb{R}_+^{L^2}$

► $\mathbf{R}_n = s \mathbf{I}$, if $\mathbf{n}_t \sim \mathcal{N}(\mathbf{0}, s \mathbf{1}_{N^2})$

► $\Omega = \{i : (\mathbf{r}_x)_i \neq 0\} = \{i : \mathbf{x}_i \neq 0\}$

$$\mathbf{R}_y \approx \frac{1}{T-1} \sum_{t=1}^T (\mathbf{y}_t - \bar{\mathbf{y}})(\mathbf{y}_t - \bar{\mathbf{y}})^T$$


$$\in \mathbb{R}_+^{N^2 \times N^2}$$

Support
Estimation



Find the pixels in the **fine grid** that contain **at least** one fluorescent molecule.
(Covariance Domain)


Intensity
Estimation



Compute intensity values for the pre-estimated support.

Support
Estimation

$$\arg \min_{\mathbf{r}_{\mathbf{x}} \in \mathbb{R}_+^{L^2}, s \in \mathbb{R}_+} \frac{1}{2} \|\mathbf{r}_{\mathbf{y}} - (\Psi \odot \Psi) \mathbf{r}_{\mathbf{x}} - s \mathbf{I}_{\mathbf{v}}\|_2^2 + \mathcal{R}(\mathbf{r}_{\mathbf{x}}; \lambda)$$

Intensity
Estimation


$$\arg \min_{\mathbf{x} \in \mathbb{R}_+^{|\Omega|}, \mathbf{b} \in \mathbb{R}_+^{N^2}} \frac{1}{2} \|\bar{\mathbf{y}} - \Psi_{\Omega} \mathbf{x} - \mathbf{b}\|_2^2 + \alpha \|\nabla_{\Omega} \mathbf{x}\|_2^2 + \beta \|\nabla \mathbf{b}\|_2^2$$

COL0RME, Support Estimation: "Hand-crafted Regularizers"


► CEL0¹: $\mathcal{R}(\mathbf{r}_{\mathbf{x}}; \lambda) = \sum_{i=1}^{L^2} \lambda - \frac{\|\mathbf{a}_i\|^2}{2} \left(|(\mathbf{r}_{\mathbf{x}})_i| - \frac{\sqrt{2\lambda}}{\|\mathbf{a}_i\|} \right)^2 \mathbb{1}_{\{|(\mathbf{r}_{\mathbf{x}})_i| \leq \frac{\sqrt{2\lambda}}{\|\mathbf{a}_i\|}\}}$

► ℓ_1 -norm: $\mathcal{R}(\mathbf{r}_{\mathbf{x}}; \lambda) = \lambda \|\mathbf{r}_{\mathbf{x}}\|_1$


► TV: $\mathcal{R}(\mathbf{r}_{\mathbf{x}}; \lambda) = \lambda \|\nabla \mathbf{r}_{\mathbf{x}}\|_{2,1}$



$\bar{\mathbf{y}} + \text{GT}$




CEL0 result²



ℓ_1 result



TV result



¹Continuous Exact ℓ_0 (CEL0) penalty ([Soubies et al., '15](#))

²An algorithmic restarting approach has been considered to improve the support reconstruction quality

Table of Contents

Introduction

COLORME

PnP-COLORME

Preliminary Results

$$\arg \min_{\mathbf{r}_{\mathbf{x}} \geq 0, s \geq 0} \mathcal{F}(\mathbf{r}_{\mathbf{x}}, s) + \lambda \mathcal{R}(\mathbf{r}_{\mathbf{x}})$$

$$\text{where } \mathcal{F}(\mathbf{r}_{\mathbf{x}}, s) = \frac{1}{2} \|\mathbf{r}_{\mathbf{y}} - (\Psi \odot \Psi) \mathbf{r}_{\mathbf{x}} - s \mathbf{I}_{\mathbf{v}}\|_2^2$$

Algorithm COLORME, Support Estimation

Require: $\mathbf{r}_{\mathbf{y}} \in \mathbb{R}^{M^4}$, $\mathbf{r}_{\mathbf{x}}^0 \in \mathbb{R}^{L^2}$, $\lambda > 0$

repeat

$$s^{k+1} = \frac{1}{M^2} \mathbf{I}_{\mathbf{v}}^\top (\mathbf{r}_{\mathbf{y}} - (\Psi \odot \Psi) \mathbf{r}_{\mathbf{x}}^k)$$

$$\mathbf{z}^{k+1} = \mathbf{r}_{\mathbf{x}}^k - \tau \nabla \mathcal{F}(\mathbf{r}_{\mathbf{x}}^k, s^{k+1})$$

$$\mathbf{r}_{\mathbf{x}}^{k+1} = \text{prox}_{\tau \lambda \mathcal{R}(\cdot)}(\mathbf{z}^{k+1})$$

until convergence

return $\Omega = \{i : (\mathbf{r}_{\mathbf{x}})_i \neq 0\}$, s

Definition of proximal operator: $\text{prox}_{\gamma \mathcal{R}(\cdot)}(\mathbf{z}) := \arg \min_{\mathbf{x} \in \mathbb{R}^{L^2}} \{\frac{1}{2} \|\mathbf{x} - \mathbf{z}\|_2^2 + \gamma \mathcal{R}(\mathbf{x})\}.$

$$\arg \min_{\mathbf{r}_{\mathbf{x}} \geq 0, s \geq 0} \mathcal{F}(\mathbf{r}_{\mathbf{x}}, s) + \lambda \mathcal{R}(\mathbf{r}_{\mathbf{x}})$$

$$\text{where } \mathcal{F}(\mathbf{r}_{\mathbf{x}}, s) = \frac{1}{2} \|\mathbf{r}_{\mathbf{y}} - (\Psi \odot \Psi) \mathbf{r}_{\mathbf{x}} - s \mathbf{I}_{\mathbf{v}}\|_2^2$$

Algorithm PnP - COL0RME, Support Estimation

Require: $\mathbf{r}_{\mathbf{y}} \in \mathbb{R}^{M^4}$, $\mathbf{r}_{\mathbf{x}}^0 \in \mathbb{R}^{L^2}$, $\lambda, \sigma > 0$

repeat

$$s^{k+1} = \frac{1}{M^2} \mathbf{I}_{\mathbf{v}}^\top (\mathbf{r}_{\mathbf{y}} - (\Psi \odot \Psi) \mathbf{r}_{\mathbf{x}}^k)$$

$$\mathbf{z}^{k+1} = \mathbf{r}_{\mathbf{x}}^k - \tau \nabla \mathcal{F}(\mathbf{r}_{\mathbf{x}}^k, s^{k+1})$$

$$\mathbf{r}_{\mathbf{x}}^{k+1} = \cancel{\text{prox}_{\tau \lambda \mathcal{R}(\cdot)}(\mathbf{z}^{k+1})} = D_{\sigma}(\mathbf{z}^{k+1})$$

until convergence

return $\Omega = \{i : (\mathbf{r}_{\mathbf{x}})_i \neq 0\}$, s

Plug-and-Play (PnP) methods (Venkatakrishnan *et al.*, '13):

Replace, within a proximal algorithm, the operator $\text{prox}_{\tau \lambda \mathcal{R}}(\cdot)$ with a more general image denoiser.

Choice of the denoiser

Use a gradient step denoiser of the form³:

$$D_{\sigma}(\mathbf{z}) = \mathbf{z} - \nabla \mathcal{R}_{\sigma}(\mathbf{z}), \quad (1)$$

where $\mathcal{R}_{\sigma} : \mathbb{R}^{L^2} \rightarrow \mathbb{R}$ is a scalar function defined by:

$$\mathcal{R}_{\sigma}(\mathbf{z}) = \frac{1}{2} \|\mathbf{z} - N_{\sigma}(\mathbf{z})\|^2, \quad (2)$$

with $N_{\sigma} : \mathbb{R}^{L^2} \rightarrow \mathbb{R}^{L^2}$ being a neural network.

³(Cohen *et al.*, '21, Hurault *et al.*, '22a, Hurault *et al.*, '22b)

Choice of the denoiser

Use a gradient step denoiser of the form³:

$$D_{\sigma}(\mathbf{z}) = \mathbf{z} - \nabla \mathcal{R}_{\sigma}(\mathbf{z}), \quad (1)$$

where $\mathcal{R}_{\sigma} : \mathbb{R}^{L^2} \rightarrow \mathbb{R}$ is a scalar function defined by:

$$\mathcal{R}_{\sigma}(\mathbf{z}) = \frac{1}{2} \|\mathbf{z} - N_{\sigma}(\mathbf{z})\|^2, \quad (2)$$

with $N_{\sigma} : \mathbb{R}^{L^2} \rightarrow \mathbb{R}^{L^2}$ being a neural network.

Convergence Guarantees

In (Hurault *et al.*, '22b), they prove that $D_{\sigma}(\mathbf{z}) = \text{prox}_{\phi_{\sigma}}(\mathbf{z})$, $\phi_{\sigma} : \mathbb{R}^{L^2} \rightarrow \mathbb{R}$ and derive convergence guarantees of the resulting PGD scheme.

In each iteration:

$$\mathcal{G}_{\sigma}(\mathbf{r}_{\mathbf{x}}^k, s^k) := \mathcal{F}(\mathbf{r}_{\mathbf{x}}^k, s^k) + \mathcal{R}_{\sigma}(\mathbf{z}^k) - \frac{1}{2} \|\mathbf{z}^k - \mathbf{r}_{\mathbf{x}}^k\|_2^2$$

³(Cohen *et al.*, '21, Hurault *et al.*, '22a, Hurault *et al.*, '22b)

Introducing a scaling parameter

Introduce *denoiser scaling* parameter⁴ $\mu > 0$:

$$D_{\mu, \sigma}(\mathbf{z}) := \frac{1}{\mu} D_{\sigma}(\mu \mathbf{z}), \quad (3)$$

⁴(Xu *et al.*, '20)

Introducing a scaling parameter

Introduce *denoiser scaling* parameter⁴ $\mu > 0$:

$$D_{\mu, \sigma}(\mathbf{z}) := \frac{1}{\mu} D_{\sigma}(\mu \mathbf{z}), \quad (3)$$

The denoiser step will now be:

$$\mathbf{r}_{\mathbf{x}}^{k+1} = D_{\mu, \sigma}(\mathbf{z}^{k+1}),$$

⁴(Xu *et al.*, '20)

Introducing a scaling parameter

Introduce *denoiser scaling* parameter⁴ $\mu > 0$:

$$D_{\mu, \sigma}(\mathbf{z}) := \frac{1}{\mu} D_{\sigma}(\mu \mathbf{z}), \quad (3)$$

The denoiser step will now be:

$$\mathbf{r}_{\mathbf{x}}^{k+1} = D_{\mu, \sigma}(\mathbf{z}^{k+1}),$$

In each iteration:

$$\mathcal{G}_{\mu, \sigma}(\mathbf{r}_{\mathbf{x}}^k, s^k) = \mathcal{F}(\mathbf{r}_{\mathbf{x}}^k, s^k) + \frac{1}{\mu^2} \mathcal{R}_{\sigma}(\mu \mathbf{z}^k) - \frac{1}{2} \|\mathbf{z}^k - \mathbf{r}_{\mathbf{x}}^k\|_2^2$$

⁴(Xu *et al.*, '20)

Table of Contents

Introduction

COLORME

PnP-COLORME


Preliminary Results

Reminder:

$$\mathbf{r}_{\mathbf{x}}^{k+1} = D_{\mu, \sigma}(\mathbf{r}_{\mathbf{x}}^k - \tau \nabla \mathcal{F}(\mathbf{r}_{\mathbf{x}}^k, s^{k+1}))$$

The denoiser takes as an input the sample auto-covariance matrix of a fluctuating temporal sequence of images.


- **Dataset:** Create different spatial patterns → Generate fluctuating sequences → Compute the temporal variance



Add Gaussian noise $\eta \sim \mathcal{N}(\mathbf{0}_{L^2}, \sigma^2 \mathbf{I}_{L^2})$, with $\sigma \sim U(0, 50/255)$.
(500 pairs of clean-noise auto-covariance images and 100 for validation)

⁵<https://github.com/samuro95/Prox-PnP>

- **Dataset:** Create different spatial patterns → Generate fluctuating sequences → Compute the temporal variance





Add Gaussian noise $\eta \sim \mathcal{N}(\mathbf{0}_{L^2}, \sigma^2 \mathbf{I}_{L^2})$, with $\sigma \sim U(0, 50/255)$.
(500 pairs of clean-noise auto-covariance images and 100 for validation)

- **Training:** We follow the procedure suggested in (Hurault *et al.*, '22) and use the code available online⁵.


⁵<https://github.com/samuro95/Prox-PnP>

Preliminary Results on Simulated Data*



* Only for deblurring ($q = 1$ and $L = N$) and using a diagonal temporal covariance matrix $\mathbf{R}_{\mathbf{y}}$.

Sensitivity to denoising and scaling parameters




Results on Experimental HD SMLM Data

- ▶ High-density Single Molecule Localization Microscopy acquisitions
- ▶ Real dataset created for the 2013 SMLM challenge
- ▶ The dataset contains $T = 500$ images, the FWHM of the PSF is 351.8 nm.

Results on Experimental HD SMLM Data

- ▶ High-density Single Molecule Localization Microscopy acquisitions
- ▶ Real dataset created for the 2013 SMLM challenge
- ▶ The dataset contains $T = 500$ images, the FWHM of the PSF is 351.8 nm.




Results on *Ostreopsis* confocal Data

- ▶ Real biological sample of the unicellular alga *Ostreopsis*
- ▶ The dataset contains $T = 500$ images, the FWHM of the PSF is 229 nm.

Results on *Ostreopsis* confocal Data

- ▶ Real biological sample of the unicellular alga *Ostreopsis*
- ▶ The dataset contains $T = 500$ images, the FWHM of the PSF is 229 nm.



Conclusion:

- ▶ A learned from the data proximal operator of a non-convex regularization function (or a Denoiser) can capture better the geometry of specific structures (e.g., filaments)

Future Work:

- ▶ Test the approach including also a down-sampling operator (Super-Resolution)
- ▶ Take into account the complete covariance matrix \mathbf{R}_y of our diffraction-limited images.

Thank you :)

e-mail: vasiliki.stergiopoulou@inria.fr

Do you have any questions?

References I



Regev Cohen, Yochai Blau, Daniel Freedman, and Ehud Rivlin, *It has potential: Gradient-driven denoisers for convergent solutions to inverse problems*, Advances in Neural Information Processing Systems (M. Ranzato, A. Beygelzimer, Y. Dauphin, P.S. Liang, and J. Wortman Vaughan, eds.), vol. 34, Curran Associates, Inc., 2021, pp. 18152–18164.



T. Dertinger, R. Colyer, G. Iyer, S. Weiss, and J. Enderlein, *Fast, background-free, 3D super-resolution optical fluctuation imaging (SOFI)*, Proceedings of the National Academy of Sciences, 106 (52) (2009), 22287–22292.



G. Dardikman-Yoffe and Y. C. Eldar, *Learned sparcom: unfolded deep super-resolution microscopy*, Opt. Express **28** (2020), no. 19, 27736–27763.



N. Gustafsson, S. Culley, G. Ashdown, D. M. Owen, P. M. Pereira, and R. Henriques, *Fast live-cell conventional fluorophore nanoscopy with ImageJ through super-resolution radial fluctuations*, Nature communications, 7(1) (2016), 12471–12471 (eng).



S. Hurault, A. Leclaire, and N. Papadakis, *Gradient step denoiser for convergent plug-and-play*, International Conference on Learning Representations, 2022.

References II



Samuel Hurault, Arthur Leclaire, and Nicolas Papadakis, *Proximal denoiser for convergent plug-and-play optimization with nonconvex regularization*, Proceedings of the 39th International Conference on Machine Learning, Proceedings of Machine Learning Research, vol. 162, PMLR, 17–23 Jul 2022, pp. 9483–9505.



Bastien Laville, Laure Blanc-Féraud, and Gilles Aubert, *Off-the-grid curve reconstruction through divergence regularisation: an extreme point result*, working paper or preprint, May 2022.



E. Soubies, L. Blanc-Féraud, and G. Aubert, *A continuous exact ℓ_0 penalty (CEL0) for least squares regularized problem*, SIAM Journal on Imaging Sciences, 8 (3) (2015), 1607–1639.



V. Stergiopoulou, L. Calatroni, J. H. de Morais Goulart, S. Schaub, and L. Blanc-Féraud, *Col0rme: Super-resolution microscopy based on sparse blinking/fluctuating fluorophore localization and intensity estimation*, Biological Imaging **2** (2022), e1.



V. Stergiopoulou, L. Calatroni, S. Schaub, and L. Blanc-Féraud, *3d image super-resolution by fluorophore fluctuations and ma-tirf microscopy reconstruction (3d-col0rme)*, 2022 IEEE 19th International Symposium on Biomedical Imaging (ISBI), 2022, pp. 1–4.



V. Stergiopoulou, J. H. de Morais Goulart, S. Schaub, L. Calatroni, and L. Blanc-Féraud, *COLORME: Covariance-based l0 super-resolution microscopy with intensity estimation*, 2021 IEEE 18th International Symposium on Biomedical Imaging (ISBI), 2021, pp. 349–352.




O. Solomon, Y. C. Eldar, M. Mutzafi, and M. Segev, *SPARCOM: Sparsity based super-resolution correlation microscopy*, SIAM Journal on Imaging Sciences, 12 (1) (2019), 392–419.




Xiaojian Xu, Jiaming Liu, Yu Sun, Brendt Wohlberg, and Ulugbek S Kamilov, *Boosting the performance of plug-and-play priors via denoiser scaling*, 2020 54th Asilomar Conference on Signals, Systems, and Computers, IEEE, 2020, pp. 1305–1312.

Preliminary results for PnP-COL0RME (Super-Resolution)



$\bar{\mathbf{y}}$



$$\hat{\Omega} = \{i : (\hat{\mathbf{r}}_{\mathbf{x}})_i \neq 0\}$$

$$\Omega = \{i : (\mathbf{r}_{\mathbf{x}})_i \neq 0\}^*$$

* For this reconstruction, only the temporal **auto**-covariances were used.

Model reformulation in the Covariance Domain

$$\mathbf{y}_t = \Psi \mathbf{x}_t, \quad \forall t = 1, \dots, T$$

$$\mathbf{y}_1 = \begin{bmatrix} \text{green} \\ \text{dark red} \\ \text{blue} \\ \text{yellow} \end{bmatrix} = \begin{bmatrix} \text{black} & \text{black} & \text{black} \\ \text{yellow} & \text{dark red} & \text{green} \\ \text{blue} & \text{black} & \text{cyan} \\ \text{brown} & \text{brown} & \text{red} \end{bmatrix} \Psi \cdots \begin{bmatrix} \text{blue} \\ \text{brown} \\ \text{dark brown} \\ \text{brown} \end{bmatrix} \mathbf{x}_1 = \begin{bmatrix} \square \\ \text{blue} \\ \square \\ \cdot \\ \cdot \\ \cdot \\ \text{yellow} \end{bmatrix}$$

Model reformulation in the Covariance Domain

$$\mathbf{y}_t = \Psi \mathbf{x}_t, \quad \forall t = 1, \dots, T$$

$$\begin{array}{c}
 \mathbf{y}_1 \\
 \begin{bmatrix} \text{green} \\ \text{red} \\ \text{blue} \\ \text{yellow} \end{bmatrix}
 \end{array}
 =
 \begin{array}{c}
 \Psi \\
 \begin{bmatrix} \text{dark blue} & \text{black} & \text{black} & \text{yellow} & \text{green} & \text{cyan} & \text{brown} & \text{red} \\ \text{dark blue} & \text{black} & \text{black} & \text{yellow} & \text{green} & \text{cyan} & \text{brown} & \text{red} \\ \text{dark blue} & \text{black} & \text{black} & \text{yellow} & \text{green} & \text{cyan} & \text{brown} & \text{red} \\ \text{dark blue} & \text{black} & \text{black} & \text{yellow} & \text{green} & \text{cyan} & \text{brown} & \text{red} \end{bmatrix}
 \end{array}
 \cdot \dots \cdot
 \begin{array}{c}
 \mathbf{x}_1 \\
 \begin{bmatrix} \text{white} \\ \text{blue} \\ \text{white} \\ \text{white} \\ \text{white} \\ \text{white} \\ \text{white} \\ \text{white} \end{bmatrix}
 \end{array}$$

$$\begin{array}{c}
 \mathbf{y}_1 \mathbf{y}_2 \dots \mathbf{y}_T \\
 \begin{bmatrix} \text{green} & \text{dark blue} & \text{dark blue} \\ \text{red} & \text{red} & \text{red} \\ \text{blue} & \text{green} & \text{blue} \\ \text{yellow} & \text{brown} & \text{brown} \end{bmatrix}
 \end{array}
 =
 \begin{array}{c}
 \Psi \\
 \begin{bmatrix} \text{dark blue} & \text{black} & \text{black} & \text{yellow} & \text{green} & \text{cyan} & \text{brown} & \text{red} \\ \text{dark blue} & \text{black} & \text{black} & \text{yellow} & \text{green} & \text{cyan} & \text{brown} & \text{red} \\ \text{dark blue} & \text{black} & \text{black} & \text{yellow} & \text{green} & \text{cyan} & \text{brown} & \text{red} \\ \text{dark blue} & \text{black} & \text{black} & \text{yellow} & \text{green} & \text{cyan} & \text{brown} & \text{red} \end{bmatrix}
 \end{array}
 \cdot \dots \cdot
 \begin{array}{c}
 \mathbf{x}_1 \mathbf{x}_2 \mathbf{x}_3 \dots \mathbf{x}_T \\
 \begin{bmatrix} \text{white} & \text{white} & \text{white} & \text{white} & \text{white} & \text{white} & \text{white} & \text{white} \\ \text{blue} & \text{dark blue} & \text{dark blue} & \text{white} & \text{white} & \text{white} & \text{white} & \text{cyan} \\ \text{white} & \text{white} & \text{white} & \text{white} & \text{white} & \text{white} & \text{white} & \text{white} \\ \text{white} & \text{white} & \text{white} & \text{white} & \text{white} & \text{white} & \text{white} & \text{white} \\ \text{white} & \text{white} & \text{white} & \text{white} & \text{white} & \text{white} & \text{white} & \text{white} \\ \text{white} & \text{white} & \text{white} & \text{white} & \text{white} & \text{white} & \text{white} & \text{white} \\ \text{white} & \text{white} & \text{white} & \text{white} & \text{white} & \text{white} & \text{white} & \text{white} \\ \text{yellow} & \text{black} & \text{brown} & \text{white} & \text{white} & \text{white} & \text{white} & \text{red} \end{bmatrix}
 \end{array}$$

Model reformulation in the Covariance Domain

$$\mathbf{y}_t = \Psi \mathbf{x}_t, \quad \forall t = 1, \dots, T$$

$$\begin{bmatrix} \mathbf{y}_1 \\ \vdots \\ \mathbf{y}_T \end{bmatrix} = \begin{bmatrix} \Psi & & \\ & \ddots & \\ & & \Psi \end{bmatrix} \begin{bmatrix} \mathbf{x}_1 \\ \vdots \\ \mathbf{x}_T \end{bmatrix}$$



$$\mathbf{R}_y = \begin{bmatrix} \mathbf{y}_1 & \mathbf{y}_2 & \dots & \mathbf{y}_T \\ \vdots & \vdots & \ddots & \vdots \end{bmatrix} = \begin{bmatrix} \Psi & & & \\ & \ddots & & \\ & & \Psi & \\ & & & \ddots \end{bmatrix} \begin{bmatrix} \mathbf{x}_1 & \mathbf{x}_2 & \dots & \mathbf{x}_T \\ \vdots & \vdots & \ddots & \vdots \end{bmatrix}$$

$$\mathbf{R}_y \approx \frac{1}{T-1} \sum_{t=1}^T (\mathbf{y}_t - \bar{\mathbf{y}})(\mathbf{y}_t - \bar{\mathbf{y}})^T \in \mathbb{R}^{N^2 \times N^2}$$

$$\mathbf{r}_x = \text{diag}(\mathbf{R}_x) \in \mathbb{R}_+^{L^2}$$

Model reformulation in the Covariance Domain

$$\mathbf{y}_t = \Psi \mathbf{x}_t, \quad \forall t = 1, \dots, T \quad \implies \quad \mathbf{R}_y = \Psi \mathbf{R}_x \Psi^T$$

$$\begin{bmatrix} \text{green} \\ \text{red} \\ \text{blue} \\ \text{yellow} \end{bmatrix} = \begin{bmatrix} \text{black} & \text{black} & \text{black} \\ \text{yellow} & \text{red} & \text{green} \\ \text{blue} & \text{cyan} & \text{red} \\ \text{brown} & \text{brown} & \text{red} \end{bmatrix} \Psi \begin{bmatrix} \text{white} \\ \text{blue} \\ \text{white} \\ \text{yellow} \end{bmatrix}$$

$$\begin{bmatrix} \text{green} & \text{red} & \text{green} \\ \text{red} & \text{red} & \text{red} \\ \text{green} & \text{green} & \text{blue} \\ \text{yellow} & \text{brown} & \text{brown} \end{bmatrix} = \begin{bmatrix} \text{black} & \text{black} & \text{black} \\ \text{yellow} & \text{red} & \text{green} \\ \text{blue} & \text{cyan} & \text{red} \\ \text{brown} & \text{brown} & \text{red} \end{bmatrix} \Psi \begin{bmatrix} \text{white} & \text{white} & \text{white} \\ \text{blue} & \text{brown} & \text{brown} \\ \text{white} & \text{white} & \text{white} \\ \text{yellow} & \text{black} & \text{brown} \end{bmatrix}$$



$$\begin{bmatrix} \text{red} & \text{green} & \text{cyan} & \text{red} \\ \text{yellow} & \text{red} & \text{brown} & \text{brown} \\ \text{green} & \text{red} & \text{green} & \text{purple} \\ \text{brown} & \text{brown} & \text{brown} & \text{green} \end{bmatrix} = \begin{bmatrix} \text{black} & \text{black} & \text{black} \\ \text{yellow} & \text{red} & \text{green} \\ \text{blue} & \text{cyan} & \text{red} \\ \text{brown} & \text{brown} & \text{red} \end{bmatrix} \Psi \begin{bmatrix} \text{white} & \text{white} & \text{white} & \text{white} \\ \text{white} & \text{white} & \text{white} & \text{white} \\ \text{white} & \text{white} & \text{white} & \text{white} \\ \text{white} & \text{white} & \text{white} & \text{white} \end{bmatrix} \begin{bmatrix} \text{blue} & \text{yellow} & \text{brown} \\ \text{white} & \text{brown} & \text{brown} \\ \text{black} & \text{cyan} & \text{red} \\ \text{white} & \text{white} & \text{white} \end{bmatrix}$$

$$\mathbf{R}_y \approx \frac{1}{T-1} \sum_{t=1}^T (\mathbf{y}_t - \bar{\mathbf{y}})(\mathbf{y}_t - \bar{\mathbf{y}})^T \in \mathbb{R}^{N^2 \times N^2}$$

$$\mathbf{r}_x = \text{diag}(\mathbf{R}_x) \in \mathbb{R}_+^{L^2}$$

Model reformulation in the Covariance Domain

$$\mathbf{y}_t = \Psi \mathbf{x}_t + \mathbf{n}_t, \quad \forall t = 1, \dots, T \implies \mathbf{R}_y = \Psi \mathbf{R}_x \Psi^T + \mathbf{R}_n$$

$$\begin{bmatrix} \mathbf{y}_1 \\ \vdots \\ \mathbf{y}_T \end{bmatrix} = \begin{bmatrix} \Psi & & \\ & \ddots & \\ & & \Psi \end{bmatrix} \begin{bmatrix} \mathbf{x}_1 \\ \vdots \\ \mathbf{x}_T \end{bmatrix}$$



$$\mathbf{R}_y = \begin{bmatrix} \Psi & & \\ & \ddots & \\ & & \Psi \end{bmatrix} \mathbf{R}_x \begin{bmatrix} \Psi^T & & \\ & \ddots & \\ & & \Psi^T \end{bmatrix}$$

$$\mathbf{R}_y \approx \frac{1}{T-1} \sum_{t=1}^T (\mathbf{y}_t - \bar{\mathbf{y}})(\mathbf{y}_t - \bar{\mathbf{y}})^T \in \mathbb{R}^{N^2 \times N^2}$$

$$\mathbf{r}_x = \text{diag}(\mathbf{R}_x) \in \mathbb{R}_+^{L^2}$$

Model reformulation in the Covariance Domain

$$\mathbf{y}_t = \Psi \mathbf{x}_t + \mathbf{n}_t + \mathbf{b}, \quad \forall t = 1, \dots, T \implies \mathbf{R}_y = \Psi \mathbf{R}_x \Psi^T + \mathbf{R}_n$$

$$\begin{bmatrix} \mathbf{y}_1 \\ \vdots \\ \mathbf{y}_T \end{bmatrix} = \begin{bmatrix} \Psi & & \\ & \ddots & \\ & & \Psi \end{bmatrix} \begin{bmatrix} \mathbf{x}_1 \\ \vdots \\ \mathbf{x}_T \end{bmatrix}$$



$$\mathbf{R}_y = \begin{bmatrix} \mathbf{y}_1 & \mathbf{y}_2 & \dots & \mathbf{y}_T \end{bmatrix} \begin{bmatrix} \Psi & & \\ & \ddots & \\ & & \Psi \end{bmatrix} \begin{bmatrix} \mathbf{x}_1 & \mathbf{x}_2 & \mathbf{x}_3 & \dots & \mathbf{x}_T \end{bmatrix}$$

$$\mathbf{R}_y \approx \frac{1}{T-1} \sum_{t=1}^T (\mathbf{y}_t - \bar{\mathbf{y}})(\mathbf{y}_t - \bar{\mathbf{y}})^T \in \mathbb{R}^{N^2 \times N^2}$$

$$\mathbf{r}_x = \text{diag}(\mathbf{R}_x) \in \mathbb{R}_+^{L^2}$$

Support
Estimation

► Covariance Domain:

$$\mathbf{y}_t = \Psi \mathbf{x}_t + \mathbf{n}_t + \mathbf{b}$$

$$\downarrow$$

$$\mathbf{R}_y = \Psi \mathbf{R}_x \Psi^T + \mathbf{R}_n$$

$$\mathbf{R}_y \approx \frac{1}{T-1} \sum_{t=1}^T (\mathbf{y}_t - \bar{\mathbf{y}})(\mathbf{y}_t - \bar{\mathbf{y}})^T \in \mathbb{R}^{N^2 \times N^2}$$

$$\mathbf{r}_x = \text{diag}(\mathbf{R}_x) \in \mathbb{R}_+^{L^2}$$

$$\mathbf{R}_n = s\mathbf{I}, s \in \mathbb{R}_+$$

Support
Estimation

► Covariance Domain:

$$\mathbf{y}_t = \Psi \mathbf{x}_t + \mathbf{n}_t + \mathbf{b}$$

$$\downarrow$$

$$\mathbf{R}_y = \Psi \mathbf{R}_x \Psi^T + \mathbf{R}_n$$

$$\mathbf{R}_y \approx \frac{1}{T-1} \sum_{t=1}^T (\mathbf{y}_t - \bar{\mathbf{y}})(\mathbf{y}_t - \bar{\mathbf{y}})^T \in \mathbb{R}^{N^2 \times N^2}$$

$$\mathbf{r}_x = \text{diag}(\mathbf{R}_x) \in \mathbb{R}_+^{L^2}$$

$$\mathbf{R}_n = s\mathbf{I}, s \in \mathbb{R}_+$$

$$\text{vec}(\cdot) \downarrow$$

$$\mathbf{r}_y = (\Psi \odot \Psi) \mathbf{r}_x + s\mathbf{I}_v$$

Support
Estimation

► Covariance Domain:

$$\mathbf{y}_t = \Psi \mathbf{x}_t + \mathbf{n}_t + \mathbf{b}$$

$$\downarrow$$

$$\mathbf{R}_y = \Psi \mathbf{R}_x \Psi^T + \mathbf{R}_n$$

$$\mathbf{R}_y \approx \frac{1}{T-1} \sum_{t=1}^T (\mathbf{y}_t - \bar{\mathbf{y}})(\mathbf{y}_t - \bar{\mathbf{y}})^T \in \mathbb{R}^{N^2 \times N^2}$$

$$\mathbf{r}_x = \text{diag}(\mathbf{R}_x) \in \mathbb{R}_+^{L^2} \quad \mathbf{R}_n = s\mathbf{I}, s \in \mathbb{R}_+$$

$$\text{vec}(\cdot) \downarrow$$

$$\mathbf{r}_y = (\Psi \odot \Psi) \mathbf{r}_x + s\mathbf{I}_v$$

- ✓ Exploit the independent statistical behaviour of the fluorescent emitters
- ✓ Shrink the PSF
- ✗ We cannot compute real intensity values

Support
Estimation



► **Covariance Domain:**

$$\mathbf{r}_y = (\Psi \odot \Psi) \mathbf{r}_x + s \mathbf{I}_v$$

► **Sparsity on \mathbf{r}_x**

Support
Estimation



► **Covariance Domain:**

$$\mathbf{r}_y = (\Psi \odot \Psi) \mathbf{r}_x + s \mathbf{I}_v$$

► **Sparsity on \mathbf{r}_x**

► **Output:** $\Omega = \{i : (\mathbf{r}_x)_i \neq 0\} = \{i : \mathbf{x}_i \neq 0\}, s$

Support Estimation




► Covariance Domain:

$$\mathbf{r}_y = (\Psi \odot \Psi) \mathbf{r}_x + s \mathbf{I}_v$$

► Sparsity on \mathbf{r}_x

► Output: $\Omega = \{i : (\mathbf{r}_x)_i \neq 0\} = \{i : \mathbf{x}_i \neq 0\}, s$

Intensity Estimation



► Image Domain:

$$\mathbf{y}_t = \Psi \mathbf{x}_t + \mathbf{n}_t + \mathbf{b}$$

► Smoothing of **signal intensities** on the estimated support Ω and smooth **background**


► Output: $\mathbf{x} = \frac{1}{T} \sum_{t=1}^T \mathbf{x}_t, \mathbf{b}$

Support Estimation



$$\arg \min_{\mathbf{r}_{\mathbf{x}} \in \mathbb{R}_+^{L^2}, s \in \mathbb{R}_+} \frac{1}{2} \|\mathbf{r}_{\mathbf{y}} - (\Psi \odot \Psi) \mathbf{r}_{\mathbf{x}} - s \mathbf{I}_{\mathbf{v}}\|_2^2 + \mathcal{R}(\mathbf{r}_{\mathbf{x}}; \lambda)$$

Intensity Estimation



$$\arg \min_{\mathbf{x} \in \mathbb{R}_+^{|\Omega|}, \mathbf{b} \in \mathbb{R}_+^{N^2}} \frac{1}{2} \|\bar{\mathbf{y}} - \Psi_{\Omega} \mathbf{x} - \mathbf{b}\|_2^2 + \mu \|\nabla_{\Omega} \mathbf{x}\|_2^2 + \beta \|\nabla \mathbf{b}\|_2^2$$

$$\arg \min_{\mathbf{r}_\mathbf{x} \in \mathbb{R}_+^{L^2}, s \in \mathbb{R}_+} \frac{1}{2} \|\mathbf{r}_\mathbf{y} - (\Psi \odot \Psi) \mathbf{r}_\mathbf{x} - s \mathbf{I}_\mathbf{v}\|_2^2 + \mathcal{R}(\mathbf{r}_\mathbf{x}; \lambda)$$



- λ : $\lambda = \gamma \lambda_{max}$, $\gamma \in (0, 1)$
 λ_{max} : a reference value, defined as the smallest regularization parameter for which the identically zero solution is found.

$$\arg \min_{\mathbf{r}_{\mathbf{x}} \in \mathbb{R}_+^{L^2}, s \in \mathbb{R}_+} \frac{1}{2} \|\mathbf{r}_{\mathbf{y}} - (\Psi \odot \Psi) \mathbf{r}_{\mathbf{x}} - s \mathbf{I}_{\mathbf{v}}\|_2^2 + \mathcal{R}(\mathbf{r}_{\mathbf{x}}; \lambda)$$

- λ : $\lambda = \gamma \lambda_{max}$, $\gamma \in (0, 1)$
 λ_{max} : a reference value, defined as the smallest regularization parameter for which the identically zero solution is found.

To avoid the dotted reconstruction (For CEL0 penalty) :

- We **restart** the algorithm repeatedly with a **new initialisation** each time, that depends but is different to the previous reconstruction.
- The final support image is the **superposition** of the multiple reconstructions.





- : Solution of **Run 1**
- +: Initialization of **Run 2**

$$\arg \min_{\mathbf{r}_{\mathbf{x}} \in \mathbb{R}_+^{L^2}, s \in \mathbb{R}_+} \frac{1}{2} \|\mathbf{r}_{\mathbf{y}} - (\Psi \odot \Psi) \mathbf{r}_{\mathbf{x}} - s \mathbf{I}_{\mathbf{v}}\|_2^2 + \mathcal{R}(\mathbf{r}_{\mathbf{x}}; \lambda)$$

- λ : $\lambda = \gamma \lambda_{max}$, $\gamma \in (0, 1)$
 λ_{max} : a reference value, defined as the smallest regularization parameter for which the identically zero solution is found.

To avoid the dotted reconstruction (For CEL0 penalty) :

- We **restart** the algorithm repeatedly with a **new initialisation** each time, that depends but is different to the previous reconstruction.
- The final support image is the **superposition** of the multiple reconstructions.



■: Solution of **Run 1**
 +: Initialization of **Run 2**

COLORME: Hyper-parameter Tuning

$$\arg \min_{\mathbf{x} \in \mathbb{R}_+^{|\Omega|}, \mathbf{b} \in \mathbb{R}_+^{N^2}} \frac{1}{2} \|\bar{\mathbf{y}} - \Psi_{\Omega} \mathbf{x} - \mathbf{b}\|_2^2 + \mu \|\nabla_{\Omega} \mathbf{x}\|_2^2 + \beta \|\nabla \mathbf{b}\|_2^2$$

- μ : We can use the **discrepancy principle**, a well-known a-posteriori parameter-choice strategy to efficiently estimate the hyper-parameter.

$$\arg \min_{\mathbf{x} \in \mathbb{R}_+^{|\Omega|}, \mathbf{b} \in \mathbb{R}_+^{N^2}} \frac{1}{2} \|\bar{\mathbf{y}} - \Psi_{\Omega} \mathbf{x} - \mathbf{b}\|_2^2 + \mu \|\nabla_{\Omega} \mathbf{x}\|_2^2 + \beta \|\nabla \mathbf{b}\|_2^2$$

- μ : We can use the **discrepancy principle**, a well-known a-posteriori parameter-choice strategy to efficiently estimate the hyper-parameter.

Discrepancy principle strategy⁶

The regularization parameter μ will be chosen such that:

$$\|\bar{\mathbf{y}} - \Psi_{\Omega} \hat{\mathbf{x}}_{\mu} - \hat{\mathbf{b}}\|_2^2 = \nu_{DP}^2 \|\bar{\mathbf{n}}\|_2^2 \quad (4)$$

$\nu_{DP} \approx 1$ is a 'safety factor', $\|\bar{\mathbf{n}}\|_2^2 = N^2 \frac{s}{T}$, s : the **estimated** noise variance.

We can define the function $f(\mu) : \mathbb{R} \rightarrow \mathbb{R}$ as:

$$f(\mu) = \frac{1}{2} \|\bar{\mathbf{y}} - \Psi_{\Omega} \mathbf{x}_{\mu} - \mathbf{b}\|_2^2 - \frac{\nu_{DP}^2}{2} \|\mathbf{e}\|_2^2 \quad (5)$$

and we want $\mu^* : f(\mu^*) = 0$.

We can find iteratively μ^* using the Newton's method:

$$\mu_{n+1} = \mu_n - \frac{f(\mu_n)}{f'(\mu_n)} \quad (6)$$

⁶Per Christian Hansen, Discrete Inverse Problems: Insight and Algorithms, Society for Industrial and Applied Mathematics, USA, 2010

COLORME: Hyper-parameter Tuning

$$\arg \min_{\mathbf{x} \in \mathbb{R}_+^{|\Omega|}, \mathbf{b} \in \mathbb{R}_+^{N^2}} \frac{1}{2} \|\bar{\mathbf{y}} - \Psi_{\Omega} \mathbf{x} - \mathbf{b}\|_2^2 + \mu \|\nabla_{\Omega} \mathbf{x}\|_2^2 + \beta \|\nabla \mathbf{b}\|_2^2$$


- β : Does not require fine tuning

Support Estimation



$$\arg \min_{\mathbf{r}_{\mathbf{x}} \in \mathbb{R}_+^{L^2}, s \in \mathbb{R}_+} \frac{1}{2} \|\mathbf{r}_{\mathbf{y}} - (\Psi \odot \Psi) \mathbf{r}_{\mathbf{x}} - s \mathbf{I}_{\mathbf{v}}\|_2^2 + \mathcal{R}(\mathbf{r}_{\mathbf{x}}; \lambda)$$

Intensity Estimation



$$\arg \min_{\mathbf{x} \in \mathbb{R}_+^{|\Omega|}, \mathbf{b} \in \mathbb{R}_+^{N^2}} \frac{1}{2} \|\bar{\mathbf{y}} - \Psi_{\Omega} \mathbf{x} - \mathbf{b}\|_2^2 + \mu \|\nabla_{\Omega} \mathbf{x}\|_2^2 + \beta \|\nabla \mathbf{b}\|_2^2$$

COLORME: Intensity and Background estimation


- ▶ Retrieves real image intensity information
(the only super-resolution method exploiting temporal fluctuations)
→ use the intensity information for **3D reconstruction** in e.g.,
MA-TIRF (Multi-Angle Total Internal Reflection Fluorescence)
microscopy acquisitions.

COL0RME: Intensity and Background estimation


- Retrieves real image intensity information
(the only super-resolution method exploiting temporal fluctuations)
→ use the intensity information for **3D reconstruction** in e.g.,
MA-TIRF (Multi-Angle Total Internal Reflection Fluorescence)
microscopy acquisitions.

- Correct artifacts:

$\bar{y} + \text{GT}$








CEL0 result



ℓ_1 result




TV result




COL0RME: Intensity and Background estimation

- ▶ Results obtained using 500 frames:



- ▶ Evaluation using the PSNR (Peak Signal-to-Noise Ratio) metric



Diffraction limited frames

Low Background & SNR ≈ 15.5 dB

Size of the image: 40 x 40

Pixel size: $0.1 \mu m$

Video rate: 100 fps

Acquisition time: 5 s

Spatial pattern: Microtubules dataset from the SMLM challenge 2016 ⁶

Temporal profiles: SOFI simulation tool (Girsault *et al.*, 2016)

⁶<http://bigwww.epfl.ch/smlm/datasets/index.html>

Diffraction limited frames

Low Background & SNR $\approx 15.5\text{dB}$


Size of the image: 40 x 40

Pixel size: $0.1\ \mu\text{m}$


Video rate: 100 fps

Acquisition time: 5 s

SOFI-tool approximation:



Temporal profile of a **single** molecule from SOFI-tool



Real Temporal profile of a pixel.

Spatial pattern: Microtubules dataset from the SMLM challenge 2016 ⁶

Temporal profiles: SOFI simulation tool (Girsault *et al.*, 2016)

⁶<http://bigwww.epfl.ch/smlm/datasets/index.html>

